

Tailgate/Toolbox Safety Training Safety Services Company-Safety Meeting Division, PO Box 6408 Yuma, AZ 85366-6408 Toll Free (866) 204-4786



| Compa | any Name: | Job Site Location: | | | |
|--|--|--|---|---|---|
| Date: | Start Time: | Finish Time: | Foreman/Su | pervisor: | |
| - ····· - | | Topic 8: | Ladder S | afetv | 777 |
| differer ladder s | uction: Ladders are an important and varieties such as straight ladders, extended simple enough to use, unsafe ladfrom a ladder can result from a nuture Unprotected ladders set up in opening zones can be bumped into or knocked Employees can slip or lose their bala | ersatile piece of equipmension ladders, fixed ladder practices can lead to ember of reasons: g doorways or high trafit over, causing a fall. | nent commonly seer ders, frame ladders, serious injuries. F | around most jobsites. Ladders come i job-built ladders, and step ladders. Al | dder use. |
| | or by over-reaching while working or If a ladder is not set up properly, it causing the person on the ladder to fa | n top of a ladder. an shift, | | There is always the hazard for a fallir from workers carrying tools or materi Weather conditions can affect safety | ig object al up a ladder. |
| For say S S S S S S S S S S S S S | side rails, defective or missing safety free of grease and oil, and no splinter binding or excessive play, wheels or If upon inspection, faulty or defective from service. The ladder may not be Use only ladders meeting length and Never use metal ladders near electric Always set up a ladder on stable, soli Never stand on the 4 top rungs of a stable hoist tools and other material up after Always observe the 3 — point rule who Never over-reach while working fro ladder's side rails. Descend and report Rungs or steps on metal ladders must include being corrugated, dimpled, konder side rails must extend 3 feet the ladder must be securely tied off a Never tie different ladders together the security of the security to the security tied off a Never tie different ladders together the security of the security tied off a Never tie different ladders together the security of the security tied off a Never tie different ladders together the security of the security tied off a Never tied of the security ti | e or defect prior to use. feet, corrosion, securely sor sharp points that mipulleys are properly lub re components are discoreturned to service untiload limit requirements al lines, equipment, or significant to extension ladder reaching the top of the en ascending or descending or descending ladder. Work with position ladder as needed at be treated to prevent sinurled, or coated with nabove the top landing, at the top to a non-move or make them longer unlines. | Inspect for broken y fitting component ay snag clothing. Cricated, and any fra vered, the ladder many larger equal to or a for the given applicated applications. Electrically the ladders on boxes, ladder, or on the top 2 see ladder. Use of too ding a ladder: keep your body within the to stay close to worldipping. Treatment toon-skid, slip-resistated this is not feasible able support and greess specifically designed. | or missing rungs or steps, broken or specifications are steps and side rails, rungs that heck that moving parts operate freely wayed or worn ropes on extension ladders as the immediately tagged and removed iginal manufacturer's specifications are cation. The Arc welding must not be done from a plocks, or crates to extend reach. Steps of a step ladder. I belts helps to manage tools while wor 2 hands and 1 foot, or 1 hand and 2 feets. The manufacturer's length, then ab rails must be provided for access. | at are vithout are replaced. metal ladder cking from a ladder. |
| recogr | Ladders must not be shifted, reposit When traveling up or down ladders, one hand to grasp the ladder, and neusion: OSHA regulations require specuize hazards relating to ladder use. Emplacement, care, and other restrictions e retrained as necessary to maintain their | always observe safe lac ver carry loads or object ific ladder safety trainin oloyees must understand in ladder handling. All r understanding of safe | Ider techniques. Alts that could cause y g. Employees who I the proper construemployees must als | ou to lose your balance and fall. use ladders must be taught to ction, appropriate selection, load to understand OSHA requirements allow these guidelines for safe ladder us | se. |
| Speci | fic Work-Site Hazards and Safety S | | | | |
| | | | | | (Name of Chemical) |
| | rial Safety Data Sheets Reviewed: _ cloyee Signatures: | (My cionature attests | and verifies my unde I that I have not suffe | rstanding of and agreement to comply with red, experienced, or sustained any recent jo | , all company safety policies |
| | | | | | |
| Fore | man/Supervisor's Signature: | | | | |

These guidelines do not supercede local, state, or federal regulations and must not be construed as a substitute for, or legal interpretation of, any OSHA regulations.